

TUBO PARA INTERCAMBIADORES DE CALOR

DIMENSIONES Y PESOS DE LOS TUBOS SEGUN NORMA ASTM A213 A269

Medidas			Diámetro Exterior	X	Espesor Mínimo	Peso Teórico	
						Min.	Max.
						(Kg/m)	(Kg/m)
1/2"	BWG	18	12,70	x	1,24	0,353	0,391
1/2"	BWG	16	12,70	x	1,65	0,453	0,502
1/2"	BWG	14	12,70	x	2,11	0,550	0,610
5/8"	BWG	16	15,87	x	1,25	0,460	0,511
5/8"	BWG	14	15,87	x	1,65	0,590	0,655
5/8"	BWG	12	15,87	x	2,11	0,727	0,807
5/8"	BWG	12	15,87	x	2,77	0,909	1,009
3/4"	BWG	18	19,05	x	1,25	0,557	0,618
3/4"	BWG	16	19,05	x	1,65	0,719	0,798
3/4"	BWG	14	19,05	x	2,11	0,895	0,993
3/4"	BWG	12	19,05	x	2,77	1,120	1,243
1"	BWG	18	25,40	x	1,25	0,750	0,832
1"	BWG	16	25,40	x	1,65	0,981	1,089
1"	BWG	14	25,40	x	2,11	1,231	1,366
1"	BWG	12	25,40	x	2,77	1,570	1,742
1 1/4"	BWG	16	31,75	x	1,65	1,244	1,380
1 1/4"	BWG	14	31,75	x	2,11	1,566	1,738
1 1/4"	BWG	12	31,75	x	2,77	2,010	2,231
1 1/2"	BWG	14	38,01	x	2,11	1,897	2,105
1 1/2"	BWG	12	38,01	x	2,77	2,444	2,713
2"	BWG	12	50,08	x	2,77	3,281	3,642

